

FEDERAL ITEM IDENTIFICATION GUIDE
PROSTHESIS, FOOT
ITEM NAME CODE
INC 68307



Commander
Defense Logistics Information Service
ATTN: DLIS-K
74 Washington Avenue North, Suite 7
Battle Creek, Michigan 49037-3084
(COMM) (269) 961-5779
(DSN) 661-5779

This Federal Item Identification Guide for Supply Cataloging is issued under the authority of Department of Defense Instruction 5025.7.

The use of this publication is mandatory for US. Federal Activities participating in Federal Catalog System Operations.

BY ORDER OF THE DIRECTOR

/s/

Commander

Defense Logistics Information Service

Table of Contents

SECTION I	6
Reply Tables	11
Reference Drawing Groups.....	15
FIIG Change List	17

INDEX OF APPROVED ITEM NAMES COVERED BY THIS FIIG

SECTION I

MRC Mode Code Requirements

NAME D ITEM NAME

Definition: A NOUN, WITH OR WITHOUT MODIFIERS, BY WHICH AN ITEM OF SUPPLY IS KNOWN.

Reply Instructions: Enter the Item Name Code applicable to this FIIG. (e.g., NAMED68307*)

MATT D MATERIAL

Definition: THE CHEMICAL COMPOUND OR MECHANICAL MIXTURE PROPERTIES OF WHICH THE ITEM IS FABRICATED.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., MATDDLRA000*)

REPLY CODE

ALB000

LRA000

PCW000

PCAH00

STA000

TTB000

WDC000

REPLY (MA01)

ALUMINUM ALLOY

LEATHER

PLASTIC POLYESTER

PLASTIC POLYURETHANE

STEEL

TITANIUM

WOOD

HUES * D COLOR

Definition: A CHARACTERISTIC OF LIGHT THAT CAN BE SPECIFIED IN TERMS OF LUMINANCE, DOMINANT WAVELENGTH, AND PURITY.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., HUESDBR0000*; HUESDBR0000\$DBE0000*; HUESDCR0000\$DBE0000*)

REPLY CODE

BE0000

BR0000

CR0000

MS0072

VY0000

REPLY (AD06)

BEIGE

BROWN

CREAM

FLESH

IVORY

ABRY J LENGTH

FIIG A545B
INC 68307
SECTION I

MRC Mode Code Requirements

Definition: A MEASUREMENT OF THE LONGEST DIMENSION OF ANY OBJECT, IN DISTINCTION FROM WIDTH.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., ABRYJAB35.000\$\$JAC37.000*)

Enter the nominal value only when a minimum and maximum are not specified. (e.g., ABRYJAA36.000*; ABRYJLA88.9*)

Table 1

A
L

REPLY (AA05)

INCHES
MILLIMETERS

Table 2

A
B
C

REPLY (AC20)

NOMINAL
MINIMUM
MAXIMUM

ABGL J WIDTH

Definition: A MEASUREMENT TAKEN AT RIGHT ANGLES TO THE LENGTH OF AN ITEM, IN DISTINCTION FROM THICKNESS.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., ABGLJAB2.375\$\$JAC2.625*)

Enter the nominal value only when a minimum and maximum are not specified. (e.g., ABGLJAA2.500*; ABGLJLA7.6*)

Table 1

A
L

REPLY (AA05)

INCHES
MILLIMETERS

Table 2

A
B
C

REPLY (AC20)

NOMINAL
MINIMUM
MAXIMUM

FEAT * G SPECIAL FEATURES

FIIG A545B
INC 68307
SECTION I

MRC Mode Code Requirements

Definition: THOSE UNUSUAL OR UNIQUE CHARACTERISTICS OR QUALITIES OF AN ITEM NOT COVERED IN THE OTHER REQUIREMENTS AND WHICH ARE DETERMINED TO BE ESSENTIAL FOR IDENTIFICATION.

Reply Instructions: Enter the reply in clear text. (e.g., FEATGQUALITY CONTROLLED*)

ZZZK * J SPECIFICATION/STANDARD DATA

Definition: THE DOCUMENT DESIGNATOR OF THE SPECIFICATION OR STANDARD WHICH ESTABLISHED THE ITEM OF SUPPLY.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the Commercial and Government Entity (CAGE) Code of the entity controlling the document, a dash, and the document designator. The agency that controls the limited coordination document must be preceded and followed by a slash following the designator. The word canceled or superseded must be preceded and followed by a slash for the designator. Professional and industrial association specifications/standards are differentiated from a manufacturer's specification in that the data has been coordinated and published by the professional and industrial association. Include amendments and revisions where applicable.

(e.g., ZZZKJT81337-30642B*;

ZZZKJS81349-MIL-D-180 REV1/CANCELED/*;

ZZZKJP80205-NAS1103*;

ZZZKJS81349-MIL-C-1140C/CE/*;

ZZZKJT81337-30642B\$\$JP80205-NAS1103*)

REPLY
CODE

REPLY (AN62)

S	GOVERNMENT SPECIFICATION
T	GOVERNMENT STANDARD
D	MANUFACTURERS SOURCE CONTROL
R	MANUFACTURERS SPECIFICATION
N	MANUFACTURERS SPECIFICATION CONTROL
M	MANUFACTURERS STANDARD
B	NATIONAL STD/SPEC
A	PROFESSIONAL/INDUSTRIAL ASSOCIATION SPECIFICATION
P	PROFESSIONAL/INDUSTRIAL ASSOCIATION STANDARD

FIIG A545B
INC 68307
SECTION I

MRC	Mode Code	Requirements
ZZZT *	J	NONDEFINITIVE SPEC/STD DATA
<p>NOTE: If the specification/standard cited in reply to MRC ZZZK is nondefinitive, reply to MRC ZZZT. This reply is the data which is not recorded in Segment C.</p> <p>Definition: THE NUMBER, LETTER, OR SYMBOL THAT INDICATES THE TYPE, STYLE, GRADE, CLASS, AND THE LIKE, OF AN ITEM IN A NONIDENTIFYING SPECIFICATION OR STANDARD.</p> <p>Reply Instructions: Enter the applicable Reply Code from Appendix A, Table 1 followed by the appropriate number, letter, or symbol. (e.g., ZZZTJTY1*; ZZZTJTY1\$\$JSTA*; ZZZTJTY1\$JSTA*)</p>		
ZZZY *	G	REFERENCE NUMBER DIFFERENTIATING CHARACTERISTICS
<p>Definition: A FEATURE OF THE ITEM OF SUPPLY WHICH MUST BE SPECIFICALLY RECORDED WHEN THE REFERENCE NUMBER COVERS A RANGE OF ITEMS.</p> <p>Reply Instructions: Enter the reply in clear text. (e.g., ZZZYGCOLOR CODED LEADS*; ZZZYGAS DIFFERENTIATED BY MATERIAL*)</p>		
CRTL *	A	CRITICALITY CODE JUSTIFICATION
<p>Definition: THE MASTER REQUIREMENT CODES OF THOSE REQUIREMENTS WHICH ARE TECHNICALLY CRITICAL BY REASON OF TOLERANCE, FIT, PERFORMANCE, OR OTHER CHARACTERISTICS WHICH AFFECT IDENTIFICATION OF THE ITEM.</p> <p>Reply Instructions: Enter the Master Requirement Code for the requirement, the reply to which renders the item as being critical. (e.g., CRTLAACKJA*; CRTLAACKJA\$\$ACSGS*)</p> <p>Reply to this requirement only if the header record for the item identification for the item being identified has been coded as critical.</p>		
PRPY *	A	PROPRIETARY CHARACTERISTICS
<p>NOTE: If Document Availability Code B, D, F, or H, reply to MRC PRPY.</p> <p>Definition: IDENTIFICATION OF THOSE CHARACTERISTICS INCLUDED IN THE DESCRIPTION FOR WHICH A NON-GOVERNMENT ACTIVITY HAS IDENTIFIED ALL OR SELECTED CHARACTERISTICS OF THE ITEM AS BEING PROPRIETARY AND THEREFORE RESTRICTED FROM RELEASE OUTSIDE THE GOVERNMENT WITHOUT PRIOR PERMISSION OF THE ORIGINATOR OF THE DATA.</p>		

FIIG A545B
INC 68307
SECTION I

MRC	Mode Code	Requirements
		Reply Instructions: Enter the MRC codes of the individual characteristics of the description which are marked proprietary on the technical data, using AND coding (\$\$) for multiple characteristics. If all the MRCs are proprietary, enter the reply PACS. If none of the MRCs is proprietary, enter the reply NPAC. (e.g., PRPYAPACS*; PRPYANPAC*; PRPYAAKJA\$\$ACSGS*)
ELRN *	G	EXTRA LONG REFERENCE NUMBER Definition: A REFERENCE NUMBER EXCEEDING 32 POSITIONS. Reply Instructions: Enter the entire reference number. Do not include the 5-position Commercial and Government Entity (CAGE) Code. (e.g., ELRNGANN112036BIL060557LEN0313605UZ062365*) If there is more than one extra long reference number on the NSN, include the CAGE or NCAGE and separate each reference by using the "&" character, (e.g., 28480 ANN112036BIL060557LEN313605UZ62365 & S1234 NN112036BIL060557LEN313605UZ62365). In determining quantity of characters in the reference number, count will be made after modification in accordance with Volume 2, Chapter 9, FLIS Procedures Manual, DoD 4100.39-M.
SUPP *	G	SUPPLEMENTARY FEATURES Definition: CHARACTERISTICS OR QUALITIES OF AN ITEM, NOT COVERED IN ANY OTHER REQUIREMENT, WHICH ARE CONSIDERED ESSENTIAL INFORMATION FOR ONE OR MORE FUNCTIONS EXCLUDING NSN ASSIGNMENT. Reply Instructions: Enter the reply in clear text. (e.g., *TOES INCLUDED*)
CXCY *	G	PART NAME ASSIGNED BY CONTROLLING AGENCY Definition: THE NAME ASSIGNED TO THE ITEM BY THE GOVERNMENT AGENCY OR COMMERCIAL ORGANIZATION CONTROLLING THE DESIGN OF THE ITEM. Reply Instructions: Enter the reply in clear text. (e.g., CXCYGLINE PROCESSOR CONTROL BOARD*)

Reply Tables

Table 1 - NONDEFINITIVE SPEC/STD DATA..... 13

FIG A545B
INC 68307

Table 1 - NONDEFINITIVE SPEC/STD DATA

<u>REPLY CODE</u>	<u>REPLY (AD08)</u>
AL	ALLOY
AN	ANNEX
AP	APPENDIX
AC	APPLICABILITY CLASS
AR	ARRANGEMENT
AS	ASSEMBLY
AB	ASSORTMENT
BX	BOX
CY	CAPACITY
CA	CASE
CT	CATEGORY
CL	CLASS
CE	CODE
CR	COLOR
CC	COMBINATION CODE
CN	COMPONENT
CP	COMPOSITION
CM	COMPOUND
CD	CONDITION
CS	CONSTRUCTION
DE	DESIGN
DG	DESIGNATOR
DW	DRAWING NUMBER
EG	EDGE
EN	END
FY	FAMILY
FG	FIGURE
FN	FINISH
FM	FORM
FA	FORMULA
GR	GRADE
GP	GROUP
BA	IMAGE COLOR
NS	INSERT
TM	ITEM
KD	KIND
KT	KIT
LG	LENGTH
LT	LIMIT
MK	MARK
AA	MARKER
ML	MATERIAL
BB	MAXIMUM DENSITY
MH	MESH
ME	METHOD
BC	MINIMUM DENSITY

<u>REPLY CODE</u>	<u>REPLY (AD08)</u>
MD	MODEL
MT	MOUNTING
NR	NUMBER
PT	PART
PN	PATTERN
PC	PHYSICAL CONDITION
PS	PIECE
PL	PLAN
PR	POINT
QA	QUALITY
RN	RANGE
RT	RATING
RF	REFERENCE NUMBER
SC	SCHEDULE
SB	SECTION
SL	SELECTION
SE	SERIES
SV	SERVICE
SX	SET
SA	SHADE
SH	SHAPE
SG	SHEET
SZ	SIZE
PZ	SPECIES
SQ	SPECIFICATION SHEET
SD	SPEED
ST	STYLE
SS	SUBCLASS
SF	SUBFORM
SP	SUBTYPE
SN	SURFACE CONDITION
SY	SYMBOL
SM	SYSTEM
TB	TABLE
TN	TANNAGE
TP	TEMPER
TX	TEXTURE
TK	THICKNESS
TT	TREATMENT
TR	TRIM
TY	TYPE
YN	UNIT
VA	VARIETY
WT	WEIGHT
WD	WIDTH

Reference Drawing Groups

No table of contents entries found.

FIIG Change List

FIIG Change List, Effective July 3, 2009

New FIIG.

APPENDIXC

